

UDE275PM


GENNEV GENERATORS SILENT SERIES

POWER OUTPUT

Prime Rating — 200 kW (250 kVA)

Standby Rating — 220 kW (275 kVA)

3-Phase, 60 Hertz, 0.8 PF



STANDARD FEATURES

- Heavy duty, 4-cycle, variable speed fan, diesel engine provides maximum reliability.
- Brushless alternator reduces service and maintenance requirements. Class H protection.
 - Open delta alternator design provides virtually unlimited excitation for maximum motor starting capability.
 - Automatic voltage regulator (AVR) provides precise regulation.
- Electronic governor system maintains frequency to $\pm 0.25\%$.
- Full load acceptance of standby nameplate rating in one step
- Soundproof, weather resistant, steel housing provides operation at 76.5dB (A) at 7meters. Fully lockable enclosure allows safety operation. Outdoor operation available.
- Internal fuel tank with direct observing glass, and fuel level meter display on control panel
- E-coat and powder coat paint provides durability and weather protection.
- Digital engine gauges including oil pressure, water temperature, battery volts, engine speed, and fuel level.
- Analog generator instrumentation including Ampere meter,
- Voltage meter, frequency meter, ammeter phase selector switch, voltmeter phase selector switch. Analog generator instrumentation and regulator adjustment.
- Deepsea/Comap professional generator controller.
 - High visibility LCD display with heated screen and alphanumeric readout.
 - IP65 Protection standard, operational temperature range of -40° to 85° C.
 - Modbus interface for gauge panel and expansion options.
 - DPF cleaningcycle indication.
 - Log record for inspection
- Automatic safety shutdown system monitors the water temperature, engine oil pressure, low coolant, low DEF, overspeed, and overcrank. Warning lights indicate abnormal conditions.
- Fuel/water separator. Removes condensation from fuel for extended engine life.
- Emergency stop switch — when manually activated, shuts down in any emergency.

GG POWER SILENT SERIES


GG POWER DECIBEL LEVEL

Normal conversation allows substantially lower operating noise levels than competitive designs. GG Gensets are at home on construction sites, in residential neighborhoods, and at hospitals

- 90 — Subway / truck traffic
- 80 — Average city traffic
- 76.5 — GG Genset at 7m
- 70 — Inside car at 60 mph
- 60 — Air conditioner at 6m
- 50 — Normal conversation

76.5
DECIBELS

GENERATOR OUTPUT PANEL



UDE275PM

GENNEV GENERATORS SILENT SERIES

SPECIFICATIONS

Generator Specifications	
Model	Revolving field, self-ventilated weatherproof
Armature Connection	Star with Neutral
Phase	3
Standby Output	220 KW (275 KVA)
Prime Output	200 KW (250 KVA)
Power Factor	0.8
Voltage Regulation (No load to full load)	±0.5%
Generator RPM	1800
Frequency	60 Hz
No. of Poles	4
Excitation	Brushless with AVR
Frequency Regulation: No Load to Full Load	Isochronous under varying loads from no load to 100% rated load
Frequency Regulation: Steady State	±0.25% of mean value for constant loads from no load to full load.
Insulation	Class H
Sound Level dB(A) Full load at 7M	76.5

Amperage	
Rated Voltage	Maximum Amps
3Ø Volt 127/220	723.7 Amps
/	/
/	/
/	/
Main Line Circuit Breaker Rating	800 Amps
Over Current Relay Trip Set Point 127/220V Mode	880 Amps

Fuel System	
Maximum Fuel Flow (per hour)	264.2 gallons (1000 liters)
Fuel Tank Capacity	132.1 gallons (500 liters)
Fuel Consumption	L / h
At full load	49.5
At 3/4 load	39.8
At 1/2 load	26.6
At 1/4 load	14.5

Control system	
Controller Brand	Deepsea
Model	DSE7320
Module	Manual/Auto start/stop module
Standard function	Engine control
	Generator monitoring
	Generator protection
	Specification
Display	Frequency
	Battery voltage
	Running hour
Warning/shutdown	under/over voltage
	under/over speed
	under/over frequency
	Low oil pressure
	High water temperature
Communication port	RS232,RS485

Engine Specifications	
Make / Model	Perkins / 1506A-E88TAG2
Emissions	/
Starting System	Electrical start
Design	4-cycle, water cooled, direct injection Turbocharged and aftercooled
Displacement	8.8 liters
No. cylinders	6
Bore x Stroke	112 x 149 mm
Gross Engine Power Output	292 hp (218 kW)
Compression Ratio	16.8 : 1
Engine Speed	1800 rpm
Overspeed Limit	2070 rpm
Oil Capacity	9.01 US gallons (41 liters)
Coolant Capacity	5.54 US gallons (21 liters)
Battery	24V 100Ah x 2

Alternator	
Alternator Brand	Mecc alte
Alternator Model	ECO38 3S4A
Excitation	Brushless, Self-Excited system
Capacity(KVA)	275kva
Power(KW)	220kw
Efficiency(%)	88%
Insulation class	Class H
Protection class	Ip23
Steady state voltage regulation	±1%
Voltage control	AVR

WARRANTY*

Generator



12 months from date of purchase or 1000 hours (whichever occurs first).

NOTICE

Enough Air flow is extremely important to Generator operation. Improper connection can cause electrocution and/or property damage. Do not connect to any electrical system except through an approved device. Specifications are subject to change without notice.


UDE275PM

GENNEV GENERATORS SILENT SERIES



Weight

Dry Weight	6,172 lbs. (2,800 kg)
Wet Weight	6,283 lbs. (2,850 kg)
Max. Lifting Point Capacity	12,345 lbs. (5,600 kg)



Manufactured for
DEEPER DISCOUNTS LLC
Email: sales@gennevgenerators.com